

Treating substrates comprises treating with dispersion of photocatalytic particles and then with siliconized compounds selected from siliconates and polyorganosiloxanes

Patent Number: FR2788707
Publication date: 2000-07-28
Inventor(s): ROCHER LAURENT; CHAUFFRIAT HENRI
Applicant(s): RHONE POULENC CHIMIE (FR)
Requested Patent: ☐ FR2788707
Application: FR19990000837 19990126
Priority Number(s): FR19990000837 19990126
IPC Classification: B05D5/08 ; B08B17/00 ; C09D5/16 ; C09D183/06 ; C09D183/16 ; C04B41/50
EC Classification:
Equivalents: AU2114200, ☐ EP1153001 (WO0044687), ☐ WO0044687

Abstract

Treating a substrate comprises dispersion of photocatalytic particles, then treating the substrate with at least a siliconized compound. Method comprises: (1) treating substrate with dispersion of photocatalytic particles; then (2) treating substrate with at least a siliconized compound selected from: (a) siliconates of formula $R-Si(OM)_m(OH)_{(3-m)}$ (I); $R = 1-18$ hydrocarbon chain optionally substituted by halogen, amino, ether, ester, epoxy, mercapto, cyano or (poly)glycol; $m = 0-3$, and $M =$ alkali metal, ammonium, phosphonium and/or condensation products of said siliconates; (b) polyorganosiloxanes of formula $M \alpha D \beta Q \delta (O1/2Ri) \iota$ (II); $M = R_{ii}3SiO1/2$; $D = R_{ii}2SiO2/2$; and $Q = SiO4/2$; in which $R_{ii} = 1-8C$ alkyl or 6-12C aryl, arylalkyl, alkylaryl or alkoxyaryl in which the aryl group is optionally substituted by 1-4C alkyl or alkoxy; $\alpha \leq 0.1$, preferably ≤ 0.01 ; $\beta \leq 0.85$; $\delta \leq 0.1$; $\alpha + \beta + \delta = 1$; $R_i = 1-4C$ alkyl; and $\iota = 0.1-1.5$; and compounds of formula $M \alpha D \beta T \psi (O1/2Ri) \iota$ (III) in which $\alpha \leq 0.2$, preferably ≤ 0.01 ; $\beta \leq 0.60$; $\psi \leq 0.3$.

Data supplied from the esp@cenet database - I2